

DELICORA[®]

GSP+



HBI

TYRES & WHEELS

www.hbi-tyres.com



DELCORA[®]

GSP+

- The new tyre standard, which will suits for a wide range of applications, from implement on mixed feeders to self-propelled wheel loaders and other industrial applications
- The construction of casing ensures a high load capacity and stability.
- The casing and the tread profile are designed with latest state of the art 3D technologies and simulations. This has results in a equal spreaded floor pressure, long lifetime and excellent self-cleaning properties



Tyre size	Ply Rating / Load - Speed Index	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	TT/TL	Recommend Rim	Max. load capacity @ 40km/h	Max. inflation pressure (Bar)
425/40B17	14/139A8	425	788	15	TL	13.00x17	2470	5.5
	22/150A8	425	788	15	TL	13.00x17	3300	9.0
445/45R19.5	137D/148A8	445	895	16	TL	14.00x19.5	3150	4.0
500/45R22.5	146D/156A8	503	1022	19	TL	16.00x22.5	4000	4.0



Head office
Hollandse Bandenmarkt Internationaal BV

Stevinweg 25 • 4691 SM Tholen • The Netherlands
 T +31 (0)166 60 10 40 • F +31 (0)166 60 10 41 • info@hbi-tyres.com

