

# DELCORA<sup>®</sup>

## SGX-1

**NEW**











# HBI

**TYRES & WHEELS**

[www.hbi-tyres.com](http://www.hbi-tyres.com)



## Available sizes

 Tyre size	 Pattern	PR/LI	TL/TT	 Rim	 Tread depth	 Overall diameter (mm)	 Section width (mm)	 Static loaded radius (mm)	 Max. load capacity (kg) 40km/h	IP (bar)
<b>275/70R22.5</b>	SGX-1	152A8	TL	7.50x22.5D	25	975	275	453	3.550	8.5
<b>315/70R22.5</b>	SGX-1	154A8	TL	7.50x22.5D	25	1016	312	472	3.750	8.5

# DEL CORA®

## SGX-1

The **NEW** Excavator Standard

- improved stability
- no spacer ring needed
- self-cleaning tread
- excellent grip
- better drive comfort
- higher fuel efficiency
- radial structure
- enhanced centre area - ideally for hard surfaces



**HBI**  
TYRES & WHEELS

**Head office**  
**Hollandse Bandenmarkt Internationaal BV**

Stevinweg 25 • 4691 SM Tholen • The Netherlands  
T +31 (0)166 60 10 40 • F +31 (0)166 60 10 41 • info@hbi-tyres.com



[www.hbi-tyres.com](http://www.hbi-tyres.com)