

THE BEST TYRE FOR WASTE & RECYCLING



BANDENMARKT®
HEAVY DUTY TYRES

WR1

HBI

TYRES & WHEELS

www.hbi-tyres.com



THE BEST TYRE FOR WASTE & RECYCLING

AVAILABLE SIZE

 Tyre size	 Pattern	PR/LI	 Rim	 Tread depth	 Overall diameter (mm)	 Section width (mm)	 Static loaded radius (mm)	 Max. load capacity 40km/h	IP (bar)
19.5R22.5 (500/70R22.5)	WR1	173A8	W14x22.5/5°	38	1235	480	555	6.500	6.0

SPECIFICATIONS

- THE NEW TYRE STANDARD FOR ALL HEAVY INDUSTRIAL APPLICATIONS, LIKE WASTE & RECYCLING
- THE ATT (ARAMIDE TYRE TECHNOLOGY) OFFERS AN EXTREME RESISTANCE TO EXTERNAL DAMAGES AND PUNCTURES
- HEAVY DUTY RUBBER COMPOUND CREATING LOWEST COST PER HOUR
- CUT RESISTANT
- PUNCTURE RESISTANT
- DRIVING COMFORT BECAUSE OF SUSPENSION
- SUSPENSION BETTER FOR UNDERCARRIAGE



A product of



Head office

Hollandse Bandenmarkt Internationaal BV

Stevinweg 25 • 4691 SM Tholen • The Netherlands

T +31 (0)166 60 10 40 • F +31 (0)166 60 10 41 • info@hbi-tyres.com

www.hbi-tyres.com

version 2021-08